



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

+

- 2MP SONY CMOS SENSOR
- Wide View 120° (f2.9mm lens)
- Wide Dynamic Range (WDR)
- Digital Noise Reduction (DNR)
- DC 12V
- Infrared LEDs for Night-time Recording
- Easy Windshield Installation with 3M Adhesive
- Simple and Secure Angle Control

To learn more about proper camera installation and deinstallation, click [here](#).

SVA045-AMWP Technical Specifications



| | | | |
|--------------------------------------|-------|---|-----|
| Synchronization | | Internal | |
| TV Mode | | PAL | |
| Power Consumption | | DC12V, 150mA | |
| Dimensions | | 80.5mm(W) x 50.5mm(D) x 61.0mm(H) | |
| Operating Temperture | | -20-c-+60°C | |
| Housing Color | Black | Mirror | Off |
| Image Sensor | | 2MP SONY CMOS SENSOR | |
| AGC | | Off / Low / Middle / High | |
| Picture Elements | | 1920 (H) x 1080 (V) | |
| Video Output | | AHD 2.0 (1080p@30/25fps) | |
| Scanning Mode | | Progressive | |
| BLC | | Off / Low / Middle / High | |
| Scan Frequency | | (V)59.94 Hz, (H)15.734 KHz (NTSC)(V)50 Hz, (H) 15.625 KHz (PAL) | |
| Infrared LED | | N/A | |
| Lens/Angle of View | | f2.9mm lens/120° | |
| Sensitivity | | 0.1 Lux | |
| S/N Ratio | | More than 50dB AGC OFF | |
| Compatible Hardware Platforms | | CP4S, CRXS | |
| Required Accessories | | CP4S: SVA-05-EXT-B CRXS: SVA-05-EXT-A | |
| Warranty | | 2-year standard | |