



HIGHLIGHTS

Commercial Grade

Ruggedized engineering to support the harsh environments of any fleet application.

High Quality

Built with premium components to ensure excellent picture quality in any conditions.

Performance Backed

All add-on cameras come with a 2-year warranty against any manufacturer's defect.

- 1.3MP SONY CMOS SENSOR
- Wide View 120° f2.9mm lens
- Digital Noise Reduction (DNR)
- DC 12V
- Infrared LEDs for Night-time Recording
- Easy Windshield Installation with 3M Adhesive
- Simple and Secure Angle Control

To learn more about proper camera installation, click [here](#).

SVA035-A Technical Specifications



Synchronization	Internal	TV Mode	NTSC
Power Consumption		DC12V, 160mA(LED ON)/100mA(LED OFF)	
Storage Temperature	-30°C ~ +80°C	Operating Temperature	-20°C-+60°C (Humidity: 10%-85% RH)
Dimensions		60.8mm(W) x 69.6mm(D) x 71.6mm(H)	
Language		English	
Housing Color	Black	Mirror	ON
Image Device		1.3 Mega-Pixel Sony CMOS Sensor	
AGC		Off / Low / Middle / High	
Picture Elements		1280 (H) x 720 (V)	
Video Output		AHD 1.0 (720p@30 / 25fps)	
Scanning Mode		Progressive	
BLC		Off / Low / Middle / High	
Infrared Spectrum		940nm	
Infrared LED		12 IR LEDs	
Lens/Angle of View		f2.9mm lens/120°	
Sensitivity		0.1Lux (F1.2,@50IRE)	
S/N Ratio		More than 50dB AGC OFF	
Compatible Hardware Platforms		CP4S, CRXS	
Required Accessories		CP4S: SVA-05-EXT-B CRXS: SVA-05-EXT-A	
Warranty		2-year standard	